



Tvářené matice jsou cenově příznivější a mají větší rozsah svěrných tloušťek.

M	OBJEDNACÍ ČÍSLO		Svěrná tloušťka S	-0,15 D	E	T	L	+0,1 P	R		
	OCEL	NEREZOVÁ OCEL									
M3	S3FR		0.3 - 1.5	4.8	0.4	5.3	8.8	4.8	-		
	S3AFR		0.5 - 2.0	5.0		5.7	9.0	5.0			
M4	S4FR	S4FRX	0.5 - 2.0	6.3	0.5	7.2	10.4	6.4	6.4		
	S4AFR	S4AFRX	0.5 - 2.5	6.0		7.0	11.0	6.0	6.0		
M5		S5FRX	0.5 - 3.0	7.1	0.5	8.1	12.0	7.2	6.0		
	S5FR		0.5 - 2.5	7.1		8.1		7.2	6.0		
	S5AFR	S5AFRX	0.5 - 2.5	7.0		8.0		7.0	6.0		
M6	S6FR	S6FRX	0.7 - 3.0	9.5	0.5	10.5	15.0	9.5	9.0		
	S6AFR	S6AFRX	0.5 - 3.0	9.0		10.0		9.0	9.0		
M8		S8FRX	0.5 - 3.0	12.6	0.6	13.6	17.0	12.7	10.0		
		S8AFRX	0.5 - 3.0	10.5		0.5		11.5	10.6	9.0	
		S8BFRX	0.5 - 3.0	11.0		0.5		12.0	11.0	9.0	
		S8FR		1.0 - 3.0	12.6	0.5	13.6	17.0	12.7	10.0	
		S8AFR		0.8 - 3.0	10.5		0.6		11.5	10.6	9.0
		S8BFR		1.0 - 3.0	11.0		0.6		12.0	11.0	9.0
M10	S10AFR	S10AFRX	1.0 - 4.0	13.0	0.6	14.1	18.5	13.0	15.0		