



Tvářené matice jsou cenově příznivější a mají větší rozsah svěrných tloušťek.

M	OBJEDNACÍ ČÍSLO		Svěrná tloušťka S	-0,1 D	+0,1 E	T	L	+0,1 P
	OCEL	NEREZOVÁ OCEL						
M3	3 TP 20FR		0.5 - 2.0	5.0	0.7	8.0	10.5	5.0
M4	4 TP 25FR	4 TP 25FRX	0.3 - 2.5	6.0	1.0	9.0	11.0	6.0
	4 TP 40FR		2.0 - 4.0					
M5	5 TP 30FR	5 TP 30FRX	0.3 - 3.0	7.0	1.0	10	13.0	7.0
			0.7 - 3.0					
M6	6 TP 30FR 6 TP 55FR	6 TP 30FRX	0.5 - 3.0	9.0	1.5	12.0	15.5	9.0
			0.8 - 3.2			13.0		
			3.5 - 5.5			12.0		
M8	8 TP 30FR 8 TP 55FR	8 TP 30FRX	0.5 - 3.0	11.0	1.5	15.0	17.5	11.0
			1.0 - 3.0			16.0		
M10	10 TPL 45FR 10 TP 30FR	*	1.5 - 4.5	13.0	2.0	19.1	24.0	13.0
			1.0 - 3.5			17.0		
M12	12 TP 40FR	*	1.0 - 4.0	16.0	2.0	21.7	25.2	16.0

* Na poptávku